

Expandet Special

Expandet Special for fixing in porous materials like aerated concrete, breeze blocks, leca®, light weight blocks etc.




AERATED CONCRETE, LIGHTWEIGHT BLOCKS & HOLLOW BRICK

ADVANTAGES

- Especially suitable for walls with plaster due to the long neck.

Type	Load capacities
DIMENSION	F_{rec}
	Recommended Load capacities kN*
G 6 x 50	0,30
G 8 x 55	0,45






* Recommended loads are maximum for a single anchor in aerated concrete PP4 independent of load direction together with largest recommended screw and without influence of edge and / or spacing. Edge distance ≥ 100 mm



NOTE]

Always use a screw which is 3 mm longer than the plug + fixture to be fixed, as the screw has to reach the plug end and draw it backwards to form a knot deep in the drilled hole.

INSTALLATION:



Expandet Special



EXPANDET SPECIAL (Technical Sheet No. 204)

TYPE DIMENSION	SCREW DIA.	DRILL DIA.	DRILL DEPTH	EXPANDET ARTICLE NO.	PCS. PER BOX	Part No	EAN 13 PER BOX
MM	MM	MM	MM				
G 6 x 50	4,0 - 5,0	6	55	660650	100	N4L1406050	5708620066011
G 8 x 55	5,5 - 6,0	8	60	660855	50	N4L1408055	5708620066028

