



# Royal Industrial Suppliers

Quality Fasteners Specialist

No. 4, M.G.S. Complex, Benki Nawab Street, S.P. Road Cross, Bangalore 560002

An ISO 9001:2015 Certified Co



8310165941 / 9008782885



sales@royalfastenersindia.com




www.royalfastenersindia.com

CATALOGUE NUMBER: **H4D15**

**HEX NUT HIGH TENSILE GR 8.8**  
**DIN 934**

**HIGH TENSILE GR 8.8 WITH ZN COATING**



Send your Orders / Enquiries along with the following Item Codes

All Dimensions are in MM

Nominal Size d Thread Size ↓	PART NO.	Width Across Corners	Width Across Flat s		Thickness m	
		e	Min	Max	Min	Max
<b>M2x0.4</b>	H4D1502000	4.32	3.82	4.00	1.35	1.60
<b>M2.5x0.45</b>	H4D1520500	5.45	4.82	5.00	1.75	2.00
<b>M3x0.5</b>	H4D1503000	6.01	5.32	5.50	2.15	2.40
<b>M4x0.7</b>	H4D1504000	7.66	6.78	7.00	2.90	3.20
<b>M5x0.8</b>	H4D1505000	8.79	7.78	8.00	3.70	4.00
<b>M6x1.0</b>	H4D1506000	11.05	9.78	10.00	4.70	5.00
<b>M8x1.25</b>	H4D1508000	14.38	12.73	13.00	6.14	6.50
<b>M10x1.5</b>	H4D1510000	18.90	16.73	17.00	7.64	8.00
<b>M12x1.75</b>	H4D1512000	21.10	18.67	19.00	9.64	10.00
<b>M14x2.0</b>	H4D1514000	24.49	21.67	22.00	10.30	11.00
<b>M16x2.0</b>	H4D1516000	26.75	23.67	24.00	12.30	13.00
<b>M18x2.5</b>	H4D1518000	29.56	26.16	27.00	14.30	15.00

Sizes in BLUE are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative.

Note: All Austenitic Stainless Steel Fasteners may exhibit some Magnetic Properties due to the Manufacturing Process.

Refer: ISO 3506-2 Annex F



# Royal Industrial Suppliers

Quality Fasteners Specialist

No. 4, M.G.S. Complex, Benki Nawab Street, S.P. Road Cross, Bangalore 560002

An ISO 9001:2015 Certified Co



8310165941 / 9008782885



sales@royalfastenersindia.com




www.royalfastenersindia.com

CATALOGUE NUMBER: **H4D15**

**HEX NUT HIGH TENSILE GR 8.8**  
**DIN 934**

**HIGH TENSILE GR 8.8 WITH ZN COATING**



Send your Orders / Enquiries along with the following Item Codes

All Dimensions are in MM

Nominal Size d Thread Size ↓	PART NO.	Width Across Corners	Width Across Flat s		Thickness m	
		e	Min	Max	Min	Max
<b>M20x2.5</b>	H4D1520000	32.95	29.16	30.00	14.90	16.00
<b>M24x3.0</b>	H4D1524000	39.55	35.00	36.00	17.70	19.00
<b>M27x3.0</b>	H4D1527000	45.20	40.00	41.00	20.70	22.00
<b>M30x3.5</b>	H4D1530000	50.85	45.00	46.00	22.70	24.00
<b>M33x3.5</b>	H4D1533000	55.37	49.00	50.00	24.70	26.00
<b>M36x4.0</b>	H4D1536000	60.79	53.80	55.00	27.40	29.00
<b>M39x4.0</b>	H4D1539000	66.44	58.80	60.00	29.40	31.00
<b>M42x4.5</b>	H4D1542000	71.30	63.10	65.00	32.40	34.00
<b>M45x4.5</b>	H4D1545000	76.95	68.10	70.00	34.40	36.00
<b>M48x5.0</b>	H4D1548000	82.60	73.10	75.00	36.40	38.00
<b>M52x5.0</b>	H4D1552000	88.25	78.10	80.00	40.40	42.00

Sizes in BLUE are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative.

Note: All Austenitic Stainless Steel Fasteners may exhibit some Magnetic Properties due to the Manufacturing Process.

Refer: ISO 3506-2 Annex F