



Royal Industrial Suppliers

Quality Fasteners Specialist

No. 4, M.G.S. Complex, Benki Nawab Street, S.P. Road Cross, Bangalore 560002

An ISO 9001:2015 Certified Co



8310165941 / 9008782885



sales@royalfastenersindia.com



www.royalfastenersindia.com

CATALOGUE NUMBER: **T2C39**

FULL THREAD ALLEN CAP SCREW DIN 912

ASTM Ti – Gr 5



Note: Head may be plain or knurled

Parameter ↓	Size →	M3x0.5	M4x0.7	M5x0.8	M6x1.0	M8x1.25	M10x1.5
Head Dia (dk)		5.50	7.00	8.50	10.00	13.00	16.00
s		2.50	3.00	4.00	5.00	6.00	8.00
k		3.00	4.00	5.00	6.00	8.00	10.00

Chemical Composition (wt%)

Classification	ASTM	Material	N	C	H	Fe	O	Al	V	Ti
TITANIUM α – β Alloy	GRADE 5	Ti -6Al – 4V	≤ 0.05	≤ 0.08	≤ 0.015	≤ 0.40	≤ 0.20	5.50- 6.75	3.50- 4.50	Bal Qty

Send your Orders / Enquiries along with the following Item Codes

All Dimensions are in MM

Length ↓	Size →	M3x0.5	M4x0.7	M5x0.8	M6x1.0	M8x1.25	M10x1.5
5		T2C3903005	T2C3904005				
6		T2C3903006	T2C3904006	T2C3905006			
8		T2C3903008	T2C3904008	T2C3905008	T2C3906008		
10		T2C3903010	T2C3904010	T2C3905010	T2C3906010		
12		T2C3903012	T2C3904012	T2C3905012	T2C3906012	T2C3908012	
16		T2C3903016	T2C3904016	T2C3905016	T2C3906016	T2C3908016	T2C3910016
20		T2C3903020	T2C3904020	T2C3905020	T2C3906020	T2C3908020	T2C3910020
25		T2C3903022	T2C3904022	T2C3905022	T2C3906022	T2C3908022	T2C3910022
30		T2C3903030	T2C3904030	T2C3905030	T2C3906030	T2C3908030	T2C3910030
35		T2C3903035	T2C3904035	T2C3905035	T2C3906035	T2C3908035	T2C3910035
40			T2C3904040	T2C3905040	T2C3906040	T2C3908040	T2C3910040
45			T2C3904045	T2C3905045	T2C3906045	T2C3908045	T2C3910045
50			T2C3904050	T2C3905050	T2C3906050	T2C3908050	T2C3910050
55						T2C3908055	T2C3910055
60						T2C3908060	T2C3910060
65						T2C3908065	T2C3910065
70						T2C3908070	T2C3910070
75						T2C3908075	T2C3910075
80						T2C3908080	T2C3910080
90						T2C3908090	T2C3910090
100						T2C3908100	T2C3910100

Sizes in BLUE are non-preferred. Availability is limited and MOQ is higher.

Data is strictly informative

Note: All Austenitic Stainless Steel Fasteners may exhibit some Magnetic Properties due to the Manufacturing Process.

Refer: ISO 3506-2 Annex F